

# SMOOTH EGG 00513 Clay Bar EN

**Detailing clay bar for mechanical removal of stubborn deposits from paintwork. It is a pliable compound which removes deeply embedded contaminants from the paint surface. Restores smoothness and prepares the body for application of wax or other products. It easily cleans paintwork of metallic particles, asphalt marks and environmental contaminants. It can also be used on rims, chrome, or glass.**

Directions: 1. Hand wash the car. Before using a clay bar, use a cleaning agent to remove metallic deposits as well as glue and asphalt. 2. Prepare a small piece of clay (~50g) by kneading it in your hands until it's soft. Form a flat shape about the size of half the palm of your hand. 3. Give the clay a good glide on the paintwork by generously applying a mix of water with a small amount of pH-neutral shampoo (10ml/1 litre of water) from a spray atomiser. 4. Rub the clay across the paint in horizontal movements until you feel the friction has become minimal. 5. Keep checking the condition of the clay. If it becomes very dirty, fold it to the inside and continue. If this is no longer possible, prepare for a new piece of clay.

**! Never resume work with a piece of clay that has fallen to the ground. This creates the risk of scratching.**

Importer:

Nowy Samochód SA,  
ul. Zbyszka Cybulskiego 3,  
00-725 Warszawa, Polska,  
T. +48 691 344 348, [info@soft99.eu](mailto:info@soft99.eu)



**SOFT99®**