

Nano Hard Plastics Coat Trial Pack

03131
EN

Extremely durable coating for protecting unpainted plastic parts. Visibly nourishes the surface, restores the original colour, and darkens the plastic. Provides a strong hydrophobic effect and protection from dirt and fading. Lasts from 6 to 12 months. Thanks to its resistance to temperatures up to 300°C, it can be used in the engine compartment and around the exhaust system.

Directions: 1. Prepare the surface by cleaning and degreasing it with dedicated products – e.g. Silicone Off. 2. Apply a small amount to the black side of the supplied applicator. 3. Spread the product evenly until a uniform effect is achieved. 4. Allow 24 hours for the product to cure completely. Do not allow contact with water or chemicals during this time. ! Full curing of the coating takes place -4 days after application.

Contains: propan-2-ol.

Highly flammable liquid and vapour, Causes serious eye irritation, May cause drowsiness or dizziness, Keep out of reach of children, Keep away from heat, hot surfaces, sparks, open flames and other ignition sources, No smoking, Avoid breathing vapours/spray, Wear protective gloves/eye protection, IF IN EYES: Rinse cautiously with water for several minutes, Remove contact lenses, if present and easy to do, Continue rinsing, Dispose of contents/container to properly labelled waste containers according to national law.

UFI: HTN8-NOR5-600N-X998

Importer:

Nowy Samochód SA,
ul. Zbyszka Cybulskiego 3,
00-725 Warszawa, Polska,
T. +48 691 344 348, info@soft99.eu

DANGER



MADE IN JAPAN

The logo for SOFT99, featuring a stylized black and white wave graphic above the text "SOFT99" with a registered trademark symbol.



4975759031314