## **Nano Hard Clear**

03144 **EN** 

Professional protective coating for compenents made of the respace plastic. It effectively protects headlights, lamp on bousings, turn indicators, or windcates naiving surface plastics, and the reduces did a dhesion. Thanks to its hydrophobic properties, it increases the effectiveness of headlights in rainy conditions,

Directions: LPrepare the surface by cleaning and degreasing it with dedicated products - e.g. Silcone Off. 2. Shake the bottle and apply the agent to the white side of the supplied applicator. S. Spread everly on the surface, A. After - I minute, when the surface with the unused white part of the sponge (the other side of the applicator, S. Leave the surface to cure for 24 hours. Do not allow contact with water or chemical during this time. Full curing of the coating takes place - days after application.

Highly flammable liquid and vapour. Toxic if swallowed, Toxic in contact with skin, May cause an allergic skin reaction. Causes serious eper intribution. Toxic if inhaled, May cause drowsines or dizziness. Causes damage to organs (optic nerve, central nervous system) (ingestion), Keep out of reach of children. Keep away from heal, hot surfaces, spanks, open flames and other ignition sources. No smoking, Wear protective glowers/forcetive obtins/gives-protection/fare protection. IF SWALLOWED. Immediately: call a POSON CENTER/doctor. F'OR SNN. Wash with pierry of water and soap. IF NNHALED. Remove person to the protection of the protection of the protection of the properly bladled waste containers according to national low.

UFI: 6XP8-70QA-6002-JQV3

DANGER

Contains: propan-2-ol; methanol; 3-trimethoxysilylpropane-1-thiol.





MADE IN JAPAN



T. +48 691 344 348, info@soft99.eu

Importer: Nowy Samochód SA, ul. Zbyszka Cybulskiego 3, 00-725 Warszawa, Polska.

4975759031444