## 09170 SILICONE OFF

FN

Silicone Off ia an inevitable product to fulfill decontamination process and prepare paint protecting it with wax, sealant or coating. It removes compound residue, old protective layers and degreases paintwork, leaving it sterile.

## Directions:

- Spray small amount of the product onto the soft microfiber cloth.
- Wipe down across the panel or ist part.
- Wait until product residue evaporates.
- 4. Repeat the pricess if needed.

Contains: hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%); cumene.

Extremely flammable aerosol, Pressurised container: May burst if heated. Causes skin irritation, May cause drowsiness or dizziness. May cause cancer. Toxic to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid release to the environment. IF exposed or concerned: Get medical advice/ attention. Protect from sunlight. Do no expose to temperatures exceeding 50°C /122°F.

Dispose of contents/container to properly labelled waste containers according to national law. RESTRICTED TO PROFESSIONAL USERS.

## UFI: 79DT-700G-V007-PVCV



Importer: Nowy Samochód S.A. ul. Zbyszka Cybulskiego 3 00-725 Warszawa Polska

+48 691 344 348 E-mail: info@soft99.eu

